




FAUX STONE PAINT SERIES



JADE LACQUER

FAUX STONE PAINT



WeChat



Whatsapp

Contact Number: **+86 189 7000 7181**

JIANGXI SAIBAOLI INDUSTRIAL CO., LTD.

Address: Foreign Investment Development District, No.5 Gongye Rd., Nanchang, Jiangxi, P.R. China

Website: www.saibaolituliao.com | email: saibaoli@outlook.com

Alibaba: jxsbl.en.alibaba.com

SAIBAOLI IMITATION STONE PAINT RESTORE THE THE TEXTURE OF REAL SFONE

Jade Lacquer

Product Introduction

Yushiqi is the next-generation flagship product in the Saibaoli stone-effect paint series. Innovatively infused with natural jade components, it uses advanced craftsmanship to exquisitely recreate the texture and luster of real jade.

Not only does it carry forward the essence of classical architectural aesthetics, but it also endows buildings with more vibrant colors, a softer texture, and superior physical and chemical performance—bringing the noble elegance of a white jade palace into modern homes.



Applications

Residential Complex / Office Building / School / Villa / Hospital

It is suitable for the decoration of the exterior walls of self-built villas, high-end residential communities, government office buildings, schools, hospitals and other buildings.



Product Features



Added Jade Like Components, Giving A Smooth And Warm Touch
 Inspired by jade, the wall surface offers a softer and smoother touch, enhancing the overall comfort of the building.

Crystal Clear Texture
 Transparent and lustrous, adding greater depth to façade colors and creating more captivating light and shadow effects.

Low VOC Formulation
 Eco-friendly and safe, odor-free during application, compliant with green building standards, and suitable for diverse environments.


Flexible And Crack Resistant
 High extensibility adapts to minor substrate deformations, ensuring resistance to cracking even under significant temperature variations or slight vibrations, with excellent durability.

High Weather Resistance
 Resist extreme climates such as ultraviolet rays, high temperatures, and severe cold, and maintain bright colors and undamaged coatings for a long time without fading or peeling.

High Hardness
 Durable and scratch-resistant, it protects the base material while enhancing the overall durability.

Stain Resistant And Waterproof
 Superior surface density for anti-permeation, easily handling rainwater and stains.

Components



Technical Data

<4H Surface dry **<8H** Touch dry **>24H** Hard dry



At an environmental temperature of 25-27°C

Thickness / 2-3 mm	Coating rate / 3-3.5Kg/m ² *	Coating layer / 1-2 times
Service life / >10 years	Color selection / Multi-color selection	Application method / Troweling
Storage conditions / <30°C,cool,dry	Specification / 20Kg/Barrel	Size / 35*25.6*39 cm

*Actual coverage will depend on the absorbency of the surface and the method of application.

System Set

01.Primer

The primer is mainly composed of nano-modified acrylic emulsion, which penetrates into the capillaries of the wall to strengthen the substrate, resist alkali, seal the surface, and improve the adhesion of the topcoat. At the same time, it enhances the moisture-proof and mildew-resistant properties of the finish.

80% Aqueous emulsion **1%** additive **19%** water

Consumption / 0.15kg/m²/Apply twice Packaging / 20Kg/Barrel
 Size / 35*25.6*39 cm Setting Time / Surface dry 2h, Hard dry 4h (25-27°C)



02.Mid Coat

Mid-coat paint is an exterior emulsion paint made from high-grade resin. It enhances the adhesion between paint layers, improves coverage, makes the coating more uniform and full, and provides a stable base for the topcoat.

30% Water-based emulsion **15%** Titanium dioxide **30%** Calcium powder

2% Additives **23%** Water

Consumption / 0.22-0.29 kg/m² Packaging / 20Kg/Barrel
 Size / 35*25.6*39 cm Setting Time / Surface dry 2h, Hard dry 4h (25-27°C)



03.Topcoat


The topcoat is formulated with special resin materials as the main component, refined with high-quality additives. It provides a strong and weather-resistant protective layer that enhances surface smoothness and gloss, while offering multiple protections such as UV resistance, scratch resistance, anti-mold, and waterproofing, thereby improving both the durability and appearance of the coating.

80% Water based silicone acrylic emulsion **2%** Additives **18%** Water

Consumption / 0.15kg/m²/Apply twice Packaging / 20Kg/Barrel
 Size / 35*25.6*39 cm Setting Time / Surface dry 2h, Hard dry 4h (25-27°C)



Construction Tools






Surface Preparation



Ensure the substrate is smooth, clean, dry, free from oil, grease, dust, and loose particles, with sufficient strength before application.

For old wall renovation: Remove loose or peeling layers, level the surface, and thoroughly clean dust, grease, and other impurities before application.

Construction Guide



Songshan Green


Note: due to the natural source of stone, it is normal that there is a little deviation in color. It is normal to pick up the goods at an interval. If there is a deviation in color, no notice will be given.




Longling Yellow




Dushan powder



Smoke green ink



Date Palm Green



Blue and White Porcelain